



Art.-Nr.:	6.0407.0252	6.0407.0501	6.0407.1003
	6.0407.1002	6.0407.1001	6.0407.2503
	6.0407.2502	6.0407.2501	6.0407.2507
	6.0407.0201	6.0407.0253	
	6.0407.0251	6.0407.0503	

0407

0407 Universal Hardener Extra Fast / Fast / Standard / Extra Slow

Properties

0407 is a versatile, UV-resistant hardener based on isocyanate for use in 2K paints, 2K primers, 2K fillers, and 2K clear coats.

Note

0407 reacts with moisture; therefore, close the container immediately after material removal. Avoid inhalation of spray mist. Stir the material thoroughly before use.

Packaging sizes

Extra Fast

- 6.0407.0252 – 4CR 0407-1 Universal Hardener – Extra fast 0.25 L
- 6.0407.1002 – 4CR 0407-1 Universal Hardener – Extra fast 1 L
- 6.0407.2502 – 4CR 0407-1 Universal Hardener – Extra fast 2.5 L

Fast

- 6.0407.0201 – 4CR 0407-2 Universal Hardener – Fast 0.2 L
- 6.0407.0251 – 4CR 0407-2 Universal Hardener – Fast 0.25 L
- 6.0407.0501 – 4CR 0407-2 Universal Hardener – Fast 0.5 L
- 6.0407.1001 – 4CR 0407-2 Universal Hardener – Fast 1 L
- 6.0407.2501 – 4CR 0407-2 Universal Hardener – Fast 2.5 L

Standard

- 6.0407.0253 – 4CR 0407-3 Universal Hardener – Standard 0.25 L
- 6.0407.0503 – 4CR 0407-3 Universal Hardener – Standard 0.5 L
- 6.0407.1003 – 4CR 0407-3 Universal Hardener – Standard 1 L
- 6.0407.2503 – 4CR 0407-3 Universal Hardener – Standard 2.5 L

Extra Slow

- 6.0407.2507 – 4CR 0407-4 Universal Hardener – Extra slow 2.5 L



Technical Data

Colour	colourless
Viscosity (20°C)	approx. 18 s (4 mm DIN 53 211)
Pot life	see base product
Mixing ratio	see base product

Storage

Store in a dry and frost-free place.

Shelf life: at least 24 months in unopened original containers.